



Features:

- 230VAC Input (European)
- MULTI OUTPUT 1: 24Vac
- OUTPUT 2: 18Vac
- Class 1 PSU (Required To Be Earthed)
- CE & EMC Compliant
- Essembled In UK
- MTBF > 50,000 Hours



Characteristics		
Part Number	T4214EP	T4511EP
Output 1 Voltage	24Vac	24Vac
Output 1 Current Max	8 x 0.5A	8 x 1A
Output 2 Voltage	18Vac	18Vac
Output 2 Current Max	100mA	100mA
Over Current Protection	8 x 0.5A Q/B Fused 1 x 0.5 Q/B Fused	8 x 1A Q/B Fused 1 x 0.5 Q/B Fused
Opertaing Temp	0 to 40 °C	
Storage Temp	-20 to 70 °C	
Input Voltage Range	230 Vac (+ / - 10%)	
Rated Frequency	50/60 Hz	
Current RMS Max	450mA	
Leakage Current	>0.25mA	
Input Fuse	T3.15A 20x5mm Time Delay Glass Fuse	
Magnetising Current	15mA	
Efficiency	90%	
MTBF	50K Hours	
Dimensions	230mm x 150mm x 85mm	
Flash Test	3.75KVAC	
Insulation I/P - O/P	500Mohm	
Certification	Low Voltage Directive - 73/23/EEC (Including 93/68/EEC) EMC Directive - 89/336/EEC (Including 92/31/EEC & 93/68/EEC)	

Case Drawings:

